

## **AQ SEAL** *Epoxy Putty*

**AQ SEAL** is a versatile, hand-kneadable, 1 : 1 ratio, easy to use, epoxy putty.

- Bonds to metal, wood, glass, concrete, fiberglass, plastics, etc.
- Soft as Clay, Cures Hard as Steel.
- Sets in 60 minutes.

### Features :

- |                             |  |
|-----------------------------|--|
| » Hardens quickly           | » Temperature Resistant                |
| » Chemical Resistant        | » Does not shrink                      |
| » Solvent Free              | » Can be drilled & painted after cure. |
| » Good Di-electric Strength | » High Mechanical Strength             |

### Uses :

Seals leakages, Patch pipes, Fill castings blow holes, Bond broken parts, plumbing, electrical insulation, Fixes damaged parts, Construction Sealant.

### Directions :

- ⇒ For best results, clean and roughen the bond area prior to application
- ⇒ Cut out the required amount with a knife , in equal weight proportions
- ⇒ Knead with fingers and briskly roll between palms to a uniform colour
- ⇒ Apply to surface to be repaired within 15 minutes of mixing
- ⇒ Force the material into any cracks or holes to be filled

### Technical Data :

WORKING LIFE .....	20 minutes
WORKING TEMPERATURE .....	100 ° C
COMPLETE CURE TIME .....	24 Hours
HARDNESS .....	80 Shores D
COMPRESSIVE STRENGTH .....	800 Kgs./sq. cm.
TENSILE SHEAR STRENGTH .....	75 Kgs./sq.cm.
FLEXURAL STRENGTH .....	450 Kgs./sq.cm.

**Packing :** Available in 100 gms, 1 Kg, and bulk packing.

### **MANUFACTURED BY :**

**AQUADRA FORSPEC PVT. LTD.**

Tel: +91 9820 393 292 / +91 98209 90182

E-mail : [aquadraforspec@gmail.com](mailto:aquadraforspec@gmail.com)

URL : <http://www.aquadra.in>