

FO-POXY (E)

EMERGENCY REPAIR COMPOUND

DESCRIPTION

Fast Cure Cold Weld Compound, for emergency repair jobs. Can be used for the all types of ferrous and non-ferrous metals for quick, and effective leak sealing applications. Used for emergency repairs in critical applications. It reduces shutdown time drastically, since it has a very low Setting time of approximately 10 minutes.

APPLICATION

Leaking pipelines, tank, Cracked sumps and pans, leaking transformers, capacitors, reactors, tubes, pumps, threaded fittings, radiators & batteries.

PROPERTIES

CURE TIME	(MINS.)	- 10
COMPRESSIVE STRENGTH	(KGS/CM²)	- 1093
TENSILE STRENGTH	(KGS/CM²)	- 250
FLEXURAL STRENGTH	(KGS/CM²)	- 530
HARDNESS	(SHORE D)	- 85
WITHSTANDING PRESSURE	(KGS/CM²)	- 100
MAXIMUM TEMPERATURE	(°C)	- 200

CHEMICAL RESISTANCE

Doesn't react with common industrial gases, acids, reagents and solvents.

ADDITIONAL INFORMATION

Can be prepared/modified as per client specification.

Packing size: 1 Kg pack / 5 Kg Pail / 20 Kg Pail

MANUFACTURED BY :

AQUADRA FORSPEC PVT. LTD.

2-A, Tower A, Viceroy Park, Kandivli (E), Mumbai - 400 101

Tel : +91 9820 393 292 / +91 98209 90182

E-mail : aquadraforspec@gmail.com

URL : <http://www.aquadra.in>