

# **FO-POXY (UW)-Rapid**

## **Rapid Set Under Water Repair Compound**

**DESCRIPTION** : Rapid Setting thick Paste / Putty consistency compound, having excellent ability for repairing and rebuilding parts or pipelines under adverse damp conditions. It is ideally used for under water repairs.

**APPLICATION** : Repair of damaged vessels, leaking Tanks, pumps, radiator leakages and pipeline leakages under damp/wet conditions. Also useful in repairing concrete and tiles under water viz. dams, swimming pools, fire water storage columns, etc.

<b><u>PROPERTIES</u></b> :	CURE TIME	(Hrs.)	-	8
	COMPRESSIVE STRENGTH	(KGS/CM <sup>2</sup> )	-	400
	TENSILE SHEAR STRENGTH	(KGS/CM <sup>2</sup> )	-	120
	FLEXURAL STRENGTH	(KGS/CM <sup>2</sup> )	-	375
	HARDNESS	(SHORE D)	-	78

**TEMP. RANGE** : UPTO 100 °C

**CHEMICAL REACTIVITY** : Doesn't react with common industrial gases, acids, reagents and solvents.

**ADDITIONAL INFORMATION** : Can be prepared as per client specification.  
Coverage Area : 1200 sq.cm./Kg for 5 mm product thickness

**MANUFACTURED BY :**

**AQUADRA FORSPEC PVT. LTD.**

2-A, Tower A, Viceroy Park, Kandivli (E), Mumbai - 400 101

Tel : +91 9820 393 292 / +91 98209 90182

E-mail : [aquadraforspec@gmail.com](mailto:aquadraforspec@gmail.com)

URL : <http://www.aquadra.in>