

# FO-POXY (WP)

## Wet Surface Repair Compound

**DESCRIPTION** : Wet Surface compound, having excellent ability for sealing, patching, repairing, bonding or coating of parts or pipelines under water. It is 100 % solid and non-polluting (0 % VOC). It has excellent adhesion with concrete, metal, wood, glass, fibreglass, etc.

**APPLICATION** : Repair of submerged parts, damaged/ leaking vessels, tank, pumps, radiator and pipeline leakages under wet conditions. It's an ideal product for waterproofing under damp condition. Also useful in repairing, patching or bonding concrete and tiles under water ; viz. in dams, irrigation canals, swimming pools, fire water storage columns, etc.

<b><u>PROPERTIES</u></b> :	POT LIFE	(MINS.)	-	20
	DRY TIME	(MINS.)	-	120
	FULL CURE TIME	(Hrs.)	-	24
	COMPRESSIVE STRENGTH	(KGS/CM <sup>2</sup> )	-	800
	TENSILE STRENGTH	(KGS/CM <sup>2</sup> )	-	300
	TENSILE SHEAR STRENGTH	(KGS/CM <sup>2</sup> )	-	100
	FLEXURAL STRENGTH	(KGS/CM <sup>2</sup> )	-	450
	HARDNESS	(SHORE D)	-	80
	WITHSTANDING TEMPERATURE	( °C)	-	100

**CHEMICAL REACTIVITY** : Doesn't react with common industrial gases, acids, alkalis and solvents.

**ADDL. INFO.** : Can be manufactured as per clients' specifications.  
Coverage Area : 1400 sq.cm./Kg for 5 mm product thickness

**MANUFACTURED BY :**

**AQUADRA FORSPEC PVT. LTD.**

2-A, Tower A, Viceroy Park, Kandivli (E), Mumbai - 400 101

Tel : +91 9820 393 292 / +91 98209 90182

E-mail : aquadraforspec@gmail.com

URL : <http://www.aquadra.in>