

Fo-Poxy (Rapid Primer)

DESCRIPTION:

Fo-Poxy (Rapid Primer) is 100% Solids specialised, fast setting, high adhesion primer system designed to improve adhesion between a large variety of coatings, metallic substrates and concrete. It acts as a barrier coat on various substrates and improves adhesion to difficult substrates such as non-ferrous metals. It can be applied over correctly prepared bare steel surfaces, fiberglass, zinc coated steel, aluminium, polyester fillers and baked acrylic enamel.

APPLICATION:

- All surfaces should be sound, clean, dry and free from oil or grease.
- Remove loose material and flaking paint.
- Brush and wash off soft or powdery surfaces.
- Remove rust and corrosion from metals.
- Abrade smooth metal, plastics and fibreglass surfaces.
- Allow 28 days for new concrete to cure and before applying primer
- Apply Primer straight from the can by brush or spray. One application will normally suffice but some highly porous substrates may require two.

TECHNICAL DATA :

Volume Solid	: 100%
Mixing Ratio	: 2 : 1 by weight
Pot Life	: 3-4 Minutes @ 25 Deg C.
Setting Time	: 5-6 Minutes Thin Film Set Time is approx 20 minutes
Wet on Wet Application	: 30 minutes Sand thoroughly if recoat interval exceeds 180 minutes
Recoat Interval	: Can be recoated / topcoated with most Coatings after 30 minutes drying at 27 Deg C and Relative Humidity below 50% as wet on wet application.
Mixed Viscosity	: Approx 12,000 cps
Adhesive Shear Strength	: 150 Kgs/ sq. cm.
Service Temperature (Max)	: 120 Deg C
Colors	: Light Grey
Packaging	: Available in 200 Kgs. Drums
Coverage	: 4-5 sq. mtrs. per Kg. mix (approx.) per coat.

Manufactured by :

AQUADRA FORSPEC PVT. LTD.

2-A, Tower A, Viceroy Park, Kandivli (E), Mumbai – 400101, Maharashtra, INDIA

Tel.: +91-22-28845705; TeleFax: +91-22-28872661

E-mail : aquadraforspec@gmail.com

Website: www.aquadra.com